



Scully Truck Identification Module™

DESCRIPTION

The Scully Truck Identification Module™ (T.I.M.®) provides a unique serial number to the Vehicle Identification Prover® (V.I.P.®) System control unit feature of the Intellitrol®, allowing the truck to communicate with the terminal during loading. The system is used in conjunction with your Scully tank overfill prevention and vehicle static grounding controls.

A tank truck enters the bay for loading and the driver attaches the loading rack overfill prevention plug to the socket. The serial number in the T.I.M. is read by the Scully Intellitrol or V.I.P. control unit and is checked for vapor tightness certification and other requirements. The overfill sensors and grounding status are also verified. If all safety is met, the truck is authorized to load.

Treminal managers may also have the ability to authorize loading of trucks not yet equipped with a T.I.M. or temporary bypass in the event of a systems failure.

FEATURES AND BENEFITS

- Eliminates driver time to present vapor tightness certificates and other documentation required by the terminal each time you load.
- Easily installs in your existing overfill prevention socket.
- Use the existing plug and cable at the rack for a single connection to provide communication.
- Prepares the truck to supply information requested by the terminal in the future.

All Dimensions in Inches

Installation Notes

TECHNICAL SPECIFICATIONS

Temperature Range: -40° to +140° F (-40° to +60° C)

Materials: Epoxy encapsulated.

Dimensions: Shown on diagram.

Approvals: Factory Mutual (FM), For use in Class 1, Division II, Group D hazardous locations in the US and Canada.



ORDERING INFORMATION

Description	Part Number
Truck Identification Module™ (T.I.M.™) for connection to V.I.P. System	08836



Copyright © 2014 Scully Signal Company. Dynacheck, Dynamic Self-Checking, Dynamic Self-Test, Faylsafe, IntelliCheck, Intellitrol, Intelliview, Load Anywhere, Maxsafety, Sculcon, and V.I.P. are registered trademarks of Scully Signal Company. All Rights Reserved. Specifications are subject to change without notice.

67211 Rev B
May 2014

Scully Signal Company
70 Industrial Way,
Wilmington, MA 01887-3479, USA
Tel: 800 272 8559 / 617 692 8600
email: sales@scully.com

Scully Systems Europe NV
Eksterveldlaan 31a
2820 Bonheiden / Belgium
Tel: +32 (0) 15 56 00 70
email: info@scully.be

Scully UK Ltd
Meridian House, Unit 33,
37 Road One Winsford Industrial Estate,
Winsford Cheshire CW7 3QG / UK
Tel: +44 (0) 1606 553805
email: sales@scullyuk.com

